

**DAK DECK T&G - PREMIUM SELECT DECKING**  
**Solid. Stable. Certified.**

**Premium Select Decking Grade Rule**

**Pattern:** Decking - NLGA Para.127 (WC200)

**Allowable Unit Stress Values:** NLGA Para. 905m.

<b><u>CHARACTERISTIC</u></b>	<b><u>PREMIUM SELECT</u></b>	<b><u>SELECT</u></b>
Checks	<b>none</b>	medium
Crook	light, occasional piece	light, occasional piece
Holes	<b>none</b>	equivalent to chipped knots
Pitch	<b>none on face</b>	light, or equivalent, very small streak
Pockets – Bark	<b>none</b>	medium
Pockets – Pitch	<b>none</b>	very small, dry
Rate of Growth	<b>light to medium</b>	medium grain
Skips (face)	<b>none</b>	very light, max 10% of face in occasional pieces
Skips (back)	<b>occasional pieces</b>	hit and miss skips full length
Slope of Grain	1 in 10	1 in 10
Splits	<b>none</b>	very light, maximum 10% of face in occasional pieces
Stained Wood	<b>light</b>	medium
Tongue	1/16” scant, occasional piece	1/16” scant, occasional piece
Torn or Raised Grain	<b>none</b>	medium
Twist	very light, occasional piece	very light, occasional piece
Knots	<b>sound &amp; tight on face &amp; back</b>	sound & tight on exposed face, well spaced
Spike & Narrow Face Knots	occasional pieces	occasional pieces
Chipped Knots & Unsound Wood	<b>none</b>	may contain chipped or unsound spots 3/4” in diameter
Back & Unexposed Edges	<b>pencil wane, occasional pieces</b> <b>no hit &amp; miss skips</b>	wane approximately 1/3 face width hit & miss skips.

***Premium Select Dak Deck T&G is:***

- manufactured in accordance with CSA 0141 and graded under the NLGA Standard Grading Rules for Canadian Lumber
- milled exclusively from the highest quality Western Canadian S-P-F and Douglas Fir sawn lumber available (J-Grade)
- manufactured to be a true reversible product to provide a structural deck for exposed ceilings/floors and roofs
- certified by COFI and end-stamped as “Premium Select Deck”
- meets or exceeds NLGA unit stress values for Select Decking (NLGA Paras. 905m and 905a to 905f).